



Corner
machinery

INTER ROW CULTIVATOR



Description

Inter row springed bladed cultivator is eliminate the weeds that is placed between plants like beets, beans, sunflowers, corn, soy, tomatoes, melons and watermelons, etc. It is a machine that provides better concentration for soil and fluffing it. By the help of this procees plansa re developed faster.

Interrow cultivator can be setted between rows. During the cultivation disks that is used to keep plant(star hairs) are blocking the small plants from covering by soil. Thanks to the structure of legs it can be easily used in stnoy lands.

Depends on size of plant that will be cultivated it is possible to setting the depth of each unit. By units independent from itself is protecting working depth on roughed lands. The guided disks that prevent a breaking the structure of deviation and direction of movement make it easy to cultivate without damage the plants.





Corner
machinery

INTER ROW CULTIVATOR



TECHNICAL FEATURES

MODEL	INTERROW mm	WEIGHT WITH TANK FERTLI- ZER kg	WEIGHT WITH NOTANK FERT- LIZER kg	LENGHT mm	WIDTH mm	HEIGHT mm	REQ. POWER hp
	450-700	535	480	2300	3000	1000	40/45
	450-700	630	560	2300	3000	1000	50-55
	450-700	685	600	2300	3500	1000	50-55
	450-700	855	760	2300	3000-4200	1000	60-70

