



### Description

Chisel with the fixed leg ,break the hard layer of field that is driven by plough on 25 depth. It saves the water and stock it on the lower parts of broken hard layer . The sotcked water are used in dry season to provide the field with required vitamines and minerals. Chisel ploughs are used after the harvesting goods and before planting the new ones.



## TECHNICAL FEATURES

|                    | Chisel  |         |         |         |         | Chisel and Roller |         |         |         |         |
|--------------------|---------|---------|---------|---------|---------|-------------------|---------|---------|---------|---------|
|                    | CM-1532 | CM-1533 | CM-1534 | CM-1535 | CM-1536 | CM-1537           | CM-1538 | CM-1539 | CM-1540 | CM-1541 |
| Quan ty Of Hand    | 5       | 7       | 9       | 11      | 13      | 5                 | 7       | 9       | 11      | 13      |
| Working Widht / mm | 1500    | 2100    | 2700    | 3000    | 3500    | 1500              | 2100    | 2700    | 3000    | 3500    |
| Working Depth / mm | 45      | 45      | 45      | 45      | 45      | 45                | 45      | 45      | 45      | 45      |
| Chassis Size / mm  | 620     | 620     | 620     | 620     | 620     | 620               | 620     | 620     | 620     | 620     |
| Weight / kg        | 260     | 355     | 445     | 570     | 700     | 480               | 590     | 700     | 840     | 970     |
| Tractor Power / Hp | 45-50   | 55-65   | 70-80   | 80-90   | 90-100  | 45-50             | 55-65   | 70-80   | 80-90   | 90-100  |