www.cornermachinery.com



Description

(Double Band System)

CORNER One Row Potato HarvesterMachine

One row processing and lifting potatoes to the rear side, Excellent soil seperation by its special"Double Band System", Works at soil conditions moreover humadity field, in winter season, Power Take Of(P.T.O.), 0,17 hectare/hour harvesting capacity (@ 2 km/h).

-Conveyor band made up of steel rods which is the risk of wear minimum level and supported by agitator rollers with bearings.

CORNER Two Rows Potato Harvester Machine With Complete Sieve System

-Absolutely, innovative, efficient, reliable, powerful.

-Simple operation of settings and for

maintanance designed for easy harvest

even in difficult conditions.

-1400 mm operational width.

-More sieving system from Corner.

-Excellent performance on both

humadity and dry field conditions.

-Extra performance at small stony and sandy fields.

-Excellent soil seperation by it's

special Complete Sieve System.

-Power take of (P.T.O.)

-0,3 hectare/hour harvesting

capacity (@ 2 km/h).

PATATO HARVESTER

www.cornermachinery.com





	CM-1631	CM-1632	СМ-1633	СМ-1634	CM-1635	CM-1636
Machine type	Sieve side dischar-ge	Pallet	Pallet and sieve	Pallet and sieve	Sieve	Pallet
Length / mm	1515	2700	2500	2750	2500	2450
Width / mm	1600	1260	1750	1750	1750	1750
Height / mm	1085	1220	1200	1200	1200	1200
Working width / mm	600	760	1400	1400	1400	1400
Number Of Rows	1	1	2	2	2	2
Working ca- pacity / hec- tare/hour	0,1	0,1	0,3	0,5	0,3	0,3
Weight / kg	400	500	750	850	700	750
Blade Type	One piece	One piece	One piece Knurled	Fragmental	One piece	Fragmental
Working speed / km/h	2	2	2	2	2	2
P.T.O.Shaft Rotations	540	540	540	540	540	540